

DENON



110
Anniversary

DEFINING AUDIO
EXCELLENCE
SINCE 1910

DENON PMA-A110 Value Electronics, Authorized Denon 110 Anniversary Dealer 914-723-3344

LIMITED SERIES DENON 110-YEAR ANNIVERSARY EDITION PMA-A110 INTEGRATED AMPLIFIER WITH 160 WATTS PER CHANNEL

Celebrating 110 years of audio excellence, Denon is proud to deliver the limited series Anniversary Edition PMA-A110 integrated amplifier featuring the latest technology to surface Hi-Fi.

HIGHLIGHTS

YOUR BENEFITS

Defining audio excellence since 1910

Denon is proud to release our limited series Anniversary Edition silver graphite flagship PMA-A110 integrated amplifier.

Anniversary Edition tuning

All Denon amplifiers boast an exceptional sound signature and this model has specially enhanced by the Denon Sound Master to celebrate our milestone anniversary.

160 Watts per channel power output (4ohm, 1kHz, THD: 0.7%)

Maximum performance to drive your favorite loudspeakers.

Trusted reputation

Includes Certificate of Authenticity signed by Denon's Head of Engineering and a 5-year, out-of-box warranty.

7th Generation Advanced Ultra High Current (UHC)-MOS Single-push-pull circuit power amplifier with Schottky barrier diodes

Enjoy wide bandwidth sound, from deep bass to detailed highs and hear every detail of your favorite songs.

Rear USB-B input for more audio format options

Hi-Res audio playback up to 384-kHz/32-bit and 11.2-MHz DSD.

Quad built-in DAC configuration for more audible power

Enjoy higher S/N ratio and audible power with a quadrupled output current from the four DAC per channel parallel configuration. Experience Hi-Res audio playback and enjoy your favorite songs in the highest quality.

Ultra AL32 Processing for an even smoother musical ride

Ultra AL32 Processing is a unique feature with data interpolation algorithm to achieve high-bit, high-sampling output performance. It is also applicable up to 1.536MHZ of audio data.

Pure analog audio reproduction

Set Analog Mode on your PMA-A110 to enjoy your music free from any digital interference.

Premium performance MM & MC phono equalizer amp

Connect your turntable and enjoy vinyl tracks.

Vibration-resistant design with Direct Mechanical Ground Construction

Hear pure, superior sound with a condensed relay for Source Direct function from the shortest signal path.

Thoughtful amplifier design with short signal paths

Hear pure, superior sound with a condensed relay for Source Direct function from the shortest signal path.

Twin transformer with separate coiled wires for audio and control circuits

Eliminates interference and optimizes sound quality with more power.

TV-Auto Standby Mode

Simply connect your TV to your PMA-A110 through either its Coaxial or Optical inputs and set to "TV-Auto-Play" to automatically switch your amplifier from music to movies.

SINCE 1910 | DEFINING AUDIO EXCELLENCE



ULTRA AL32
PROCESSING





Denon Celebrates 110-Years of Defining Audio Excellence
 Celebrate 110 years of defining audio excellence with the Denon limited series Anniversary Edition silver graphite PMA-A110 integrated amplifier. Denon has been upgrading your expectations in the audio and video industry since 1910 and we are proud to celebrate this milestone achievement with the PMA-A110.

High Power 160W Integrated Amplifier
 Power the most demanding loudspeaker with the Denon PMA-A110 integrated amplifier. Engineered with excellence in mind, the PMA-A110 delivers 160 Watts of power-per-channel (4ohm, 1kHz, THD: 0.7%). This integrated amplifier offers compatibility with the widest range of speaker types and impedances for operational stability.

Designed with Your Expectations as Our Beginning
 Denon's new PMA-A110 was designed to exceed your expectations with previous amplifiers. With its limited series Anniversary Edition silver graphite color, aluminum feet, double layer steel transformer plate, and new premium back panel and speaker panels, the PMA-A110 is specially crafted for the most dedicated audiophile. Designed and engineered with masterful precision and refinement in mind, the PMA-A110 offers the most defined audio experience.

Certificate of Authenticity and 5-Year Warranty
 With your purchase of the limited edition PMA-A110, you will receive a Certificate of Authenticity signed by Denon's Head of Engineering. You will receive a special, 5-year out-of-box warranty.

7th Generation Advanced Ultra High Current MOS Single Push-Pull Circuit
 The PMA-A110 features a new generation of Advanced UHC (Ultra High Current)-MOS Single Push-Pull circuit design, which combines with a differential 2-stage amplifier circuit to achieve a high-current amplifier able to drive almost any speaker configuration with improved sound quality. To achieve impeccable balance between delicate details of music reproduction and vigor of low frequency sound, the PMA-A110 is capable of delivering a massive current output in a single push-pull configuration to drive even the most demanding speaker and ensure superior linearity in the output stage.

High Precision Electrical Controls
 The PMA-A110 embraces electrical volume, balance and tone controls while preserving the analog feeling of operation. Clever engineering offers the feel of an analog volume knob while an MCU measures the position of the knob and converts that position to control the master volume digitally. This unique mechanism offers a smoother, more linear control of the master volume by adjusting the curve of the analog volume control in the digital world. The same configuration is also used for Balance and Tone controls.

High-Grade Audio Components
 Denon engineers carefully constructed the amplifier circuit within the PMA-A110 to secure a frequency response of up to 100-kHz

during applied use. The volume circuit suppresses noise in the amplifier, achieving high sonic resolution. The PMA-A110 handles a wide, dynamic range of Hi-Res audio sources with tone control and power throughout. In addition, the Quad D/A converter which uses the Burr Brown PCM1795 chip operates in a quadruple configuration for optimal high-grade sound. Each channel has two PCM1795 chips working in a different mode to achieve the highest accuracy and best signal to noise ratio.

USB-DAC supporting 11.2-MHz DSD and 384-kHz/32-bit PCM
 To accurately synchronize its digital circuits, the PMA-A110 provides a USB-DAC input for Hi-Res audio functions that support Hi-Res up to 11.2-MHz DSD and 384-kHz/32-bit PCM input signals. Crafted with exceptional quality, the DAC suppresses jitter and ensures optimal precision in D/A conversion. In addition, the DSD transmission methods support Wasapi, ASIO native playback and DSD Audio over PCM Frames (DoP). The D/A converter used in the PMA-A110 is the same 384-kHz/32-bit and DSD capable premium DAC used in the DCD-A110 to deliver a clean, high-grade sound.

Ultra AL32 Processing with 384-kHz/32-bit Support
 The PMA-A110 is equipped with Ultra AL32 Processing, the latest in analog waveform reproduction technology from Denon. Ultra AL32 Processing utilizes data interpolation algorithms and also supports Hi-Res 384-kHz/32-bit PCM signal input. These algorithms interpolate points that should exist before and after the points in large quantities of data to achieve a smooth waveform that is close to that of the original signal.

These algorithms upsample the bandwidth from the original content, smoothing out the waveform and improving sound reproduction. Ultra AL32 Processing doubles the processing bandwidth from the previous generation upsampling 384-kHz content to 1.536-MHz. By carefully restoring data that was lost during digital recording, the resulting playback sound is highly detailed, free of interference, accurately localized, richly expressive in the lower range, and beautifully faithful to its original sound.

DAC Master Clock Design
 To accurately synchronize digital circuits and the four audio DACs, the PMA-A110's Master Clock Design adopts a Dual Low Phase Noise Oscillator which positions the master clock immediately adjacent to the D/A converters (DAC) suppressing jitter and ensuring optimum precision in D/A conversion.

In addition, the quality of the clock, which becomes the reference for semiconductor operation, is extremely important for ensuring that the digital audio circuitry performs at its maximum potential. The PMA-A110 employs a clock oscillator to dramatically reduce phase noise that is can cause displacement of frequencies. The PMA-A110 is further equipped with two clock oscillators, one for each sampling frequency (44.1-kHz and 48-kHz), that can be switched between the frequencies to thoroughly suppress jitter.

USB-B, Optical and Coaxial Digital Inputs
 The PMA-A110 features a USB-B input to directly connect a computer and supports PCM signal 384-kHz/32-bit and 11.2-MHz DSD. Use the USB-B input to listen to Hi-Res audio recording from an audio source on your computer in native mode. You can also take advantage of three Optical inputs and one Coaxial input to support PCM 192-kHz/24-bit. These digital inputs improve sound quality of your TV audio, Blu-ray, media players and more.

Digital Isolator and Pure Analog Mode
 Combining the best of both the analog and digital world, the PMA-A110 is equipped with a high-speed digital isolator circuit between both sections to avoid any interference from the digital world in the analog domain. The PMA-A110 also features three independent power supplies to ensure complete isolation for each section and avoid any interference. When the PMA-A110 is set to Pure Analog Mode it turns off all digital circuits for the perfectly clear sound reproduction of an analog input signal. Pure Analog Mode also turns off the fluorescent display, allowing the PMA-A110 to operate as a purely analog amp (during Pure Analog Mode, USB-B, coaxial digital, and optical digital inputs are disabled) and remove any electrical disturbances that may adversely effect your listening experience.

Robust power supply circuitry
 The PMA-A110 is equipped with two transformers that have been mounted facing opposite directions in a leakage cancelling (LC) mount system to cancel mutual influences of magnetic flux, a source of noise, leaking from the transformers. Denon's new, custom-designed, powerful large-capacity electrolytic capacitors have been used for rectification, and low-loss, low-noise, high-speed Schottky Barrier Diodes have been used in the rectifier circuitry. This ensures a sufficient supply of clean current. To achieve a "simple & straight" circuit configuration, the connection unit between the diode unit and the block capacitor has been removed to drastically shorten the current supply line to the power amp. Extremely thick OFC wiring material has been used for the power line to reduce impedance.

MM and MC Phono Equalizer
 The PMA-A110 includes a phono input that supports both MM and MC cartridges for complete enjoyment of your entire vinyl collection. The PMA-A110 phono equalizer is a CR type that is superior sonically to the NF type phono equalizer. It is exceptionally stable in the high frequency range and is able to reproduce superior sound especially when a high-quality cartridge like the DL-A110 is used.

External pre-amp input terminals
 The PMA-A110 provides "EXT.PRE" input terminals - fixed gain inputs - that can be used for connecting an external pre-amp and using the PMA-A110 as a power amp. This is convenient when connecting an A/V amp via its pre-outs so that the listening space with the same front speakers can be used as a home theater.

Technical Information	
Power Amplifier Section	
Rated Power	80W + 80W (8 ohm, 20Hz-20kHz, THD: 0.07%) 160W + 160W (4 ohm, 1kHz., THD: 0.7%)
Total Harmonic Distortion	.01% (Rated Output -3dB) 8ohm 1kHz
Input Sensitivity MM	2.5 mV / 47 kohm
Input Sensitivity MC	200 µV / 100 ohm
SN Ratio MM/MC	84 dB / 72 dB
Input Sensitivity	135 mV/17 kohms
Sign to Noise Ratio	107 dB
RIAA Deviation	20Hz - 20kHz +/-0.5dB
Tone Controls	
Bass	Yes
Treble	Yes
Balance	Yes
General	
Power Supply	NA - AC 120V, 60kHz EU - AC 230V, 50/60Hz
Power Consumption	400W
Standby Consumption	0.2W
Maximum Dimensions (W x D x H)	17.1" x 17.7" x 7.1"
Carton Dimensions (W x D x H)	22.7" x 22" x 12.8"
Weight in LBS	55.1 LBS
Weight in LBS (Packaging)	66.6 LBS
Maximum Dimensions (W x D x H)	434 x 450 x 182
Carton Dimensions (W x D x H)	577 x 560 x 325
Weight in kg	25 kg
Weight in kg (Packaging)	30.2 kg

Ports		
In	Phono (MM / MC)	x1
	Digital in: USB-B / Optical / Coaxial	1 / 3 / 1
	Audio Inputs	x5
Out	Audio out	X1
	Headphone out	x1
	Speaker Terminal	2

**Value Electronics
 Authorized Dealer
 914-723-3344**

www.ValueElectronics.com