

# Technics SU-G700M2 Grand Class Intergrated Amp



## Stereo Integrated Amplifier SU-G700M2 Specifications SU-G700M2 Silver and SU-G700M2-k Black

**Value Electronics**  
Authorized Technics Dealer

### Output Power

---

70W + 70W ( 1kHz, T.H.D. 0.5 %, 8 $\Omega$ , 20kHz LPF )  
140W + 140W ( 1kHz, T.H.D. 0.5 %, 4 $\Omega$ , 20kHz LPF )

---

### FTC Output Power

---

70W + 70W ( 1kHz, T.H.D. 0.5 %, 8 $\Omega$ , 20kHz LPF )  
140W + 140W ( 1kHz, T.H.D. 0.5 %, 4 $\Omega$ , 20kHz LPF )

---

### Load Impedance

---

4 $\Omega$ -16 $\Omega$

---

### Frequency Response

---

**PHONO (MM)** 20Hz - 20kHz ( RIAA DEVIATION  $\pm$ 1dB, 8 $\Omega$  )

---

**PHONO (MC)** 20Hz - 20kHz ( RIAA DEVIATION  $\pm$ 1dB, 8 $\Omega$  )

---

**LINE** 5Hz - 80kHz ( -3dB, 8 $\Omega$  )

---

**DIGITAL** 5Hz - 80kHz ( -3dB, 8 $\Omega$  )

---

### Input Sensitivity / Input Impedance

---

**PHONO (MM)** 2.5 mV / 47 k $\Omega$

---

**PHONO (MC)** 300  $\mu$ V / 100  $\Omega$

---

**LINE** 200 mV / 22 k $\Omega$

---

### Analogue Input Terminal

---

LINE x 2 (LINE1, LINE2 / MAIN IN)  
PHONO (MM/MC) x1

---

## Digital Input Terminal

---

Optical digital x2 (OPT 1, OPT 2)  
Coaxial digital x2 (COAX 1, COAX 2)  
USB-B x1 (PC)

---

## Analogue Output Terminal

---

LINE OUT x1 (LINE OUT)  
PRE OUT x1 (PRE OUT)

---

## Headphone Output

---

Yes, Stereo  $\Phi$ 6.3 mm

---

## PC(USB-B)

---

USB 2.0 high-speed  
USB Audio Class 2.0, Asynchronous mode

---

## Support Codec

---

PCM Yes (32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit)  
DSD Yes (2.8 MHz, 5.6 MHz, 11.2 MHz)

---

## DSD control mode

---

ASIO Native mode, DoP mode

---

## Power Supply

---

AC 120 V ,60 Hz

---

## Power Consumption

---

95W

---

## Dimensions (W x H x D)

---

16-15/16 x 5-13/16 x 16-27/32 inch

---

## Weight

---

Approx. 28 lbs

---