

Pro Cinema LS12000 4K PRO-UHD^{®1} Laser Projector

3-Chip 3LCD Laser Projector with HDR10+² and UltraBlack™ Technology

Specifications

Projection System Epson 3LCD
Chip Design (Architecture) 3-Chip
Light Source True Laser Diode Array
Projection Method Front, Front-Ceiling, Rear, Rear-Ceiling
Product Color Black
Driving Method Poly-silicon TFT Active Matrix, 0.74"-wide panel, 12-bit
Output Resolution 4K PRO-UHD¹ 3840 x 2160 (dual-axis: 1920 x 1080)
Maximum Input Resolution 4096 x 2160
Maximum Refresh Rate 120 Hz
Supported Resolutions 4K 2160p, 2K Full HD 1080p/i, HD 720p, 576p/i, 480p/i
Native Aspect Ratio 16:9 widescreen
Resize Aspect Ratio Support 1.9:1 (4096 x 2160), 21:9 (2560 x 1080), 4:3 (1600 x 1200), 9:6 (720 x 480), 5:4 (720 x 576); compatible with Normal, Full or Zoom Modes
Color Brightness³ Color Light Output: 2,700 lumens
White Brightness³ White Light Output: 2,700 lumens
Contrast Ratio Up to and over 2,500,000:1, Auto Iris on
White Balance 14-point temperature adjustment
Color Reproduction Full-color (up to 1.07 billion colors)
Size (Projected Distance) 50" to 300" (at 58" to 62.4")
Keystone Correction Vertical/Horizontal: ± 30 degrees
HDR Color Processing Full 10-bit
Epson ZX Picture Processor Full 12-bit
Light Source Life⁵
 Normal Mode: Up to 20,000 hours
 Medium Mode: Up to 20,000 hours
 Eco Mode: Up to 20,000 hours

Projection Lens

Epson VRX Lens 15-element precision glass structure (AGS)
Type Powered focus/optical zoom/lens position
F-number 2.0 – 3.0
Focal Length 22.5 – 46.7 mm
Zoom Ratio 1 – 2.1
Throw Ratio Range 1.35 – 2.84
Lens Shift
 Vertical: -96.3% to +96.3% (H center, powered)
 Horizontal: -47.1% to +47.1% (V center, powered)
Lens Cover Powered, slide lens shutter

Interfaces

2x HDMI[®] 2.1 (HDCP 2.3); one supporting eARC/ARC
 1x USB Type-A (for optical HDMI cable, 300 mA maximum power supply only)
 1x USB Type-A 5 V, 2.0 A for power and firmware
 1x Mini USB (service only)
 1x LAN RJ45
 1x RS-232C
 1x Trigger out (On, Off) 12 V DC, 200 mA maximum



Other Features

Dynamic Range Support HDR10², HDR10+², HLG
HDR² Adjustment 16 steps, real-time
Color Modes Dynamic, Vivid, Bright Cinema, Cinema, Natural, B&W Cinema
Aspect Adjustment Yes (Auto/Full/Zoom/Anamorphic Wide/Horizontal Squeeze)
Anamorphic Lens Option Compatible with third party; Anamorphic Lens Kit sold separately
Frame Interpolation Input up to 4K at 60 Hz, output up to 4K at 120 Hz
eARC Audio Compatibility LPCM, supports Dolby[®] Digital AC-3, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos, DTS, DTS-HD, DTS-HD High Resolution Audio, Master Audio, DTS:X, AAC
ARC Audio Compatibility LPCM, Dolby Digital (AC-3), DTS, AAC
Computer Compatibility PC, Mac[®]
Operating Temperature 41° to 95° F (5° to 35° C)
Power Supply Voltage 100 – 240 VAC ± 10%, 50/60 Hz
Power Consumption
 Normal Mode: 311 W
 Medium Mode: 243 W
 Eco Mode: 204 W
Fan Noise 22 – 30 dB
Security Kensington[®] security lock port
Parental Controls Power Button Lock hinders projector from being turned on without parental supervision

Dimensions (W x D x H)
Projector, including feet (excluding cable cover)
 20.5" x 17.6" x 7.6"
 Weight: 28.0 lb
 Packaging: 27.8" x 21.9" x 16.0"
 Weight: 50.8 lb

Remote Control

Features Front and rear directional
Operating Distance 32 ft (10 m)
Operating Angle
 Front Right/Left: ± 30 degrees
 Upper/Lower: ± 30 degrees
 Rear Right/Left: ± 30 degrees
 Upper/Lower: 0 + 60 degrees

Support

Epson ConnectionSM
 Pre-sales support: U.S.: 800-463-7766, Canada: 800-807-7766
 Website: U.S.: www.epson.com, Canada: www.epson.ca
Service Programs 3-year projector limited warranty, Extra CareSM Home Service program, PrivateLine[®] dedicated toll-free support (U.S. and Canada only)

What's in the Box

Pro Cinema LS12000 projector, ceiling mount, cable cover, power cord, remote control with (2) AA batteries, Quick Setup Guide

Eco Features

RoHS compliant
 Recyclable product⁶
 Epson America, Inc. is a SmartWay[®] Transport Partner⁷

Ordering Information

Pro Cinema LS12000 V11HA47020MB
 Replacement Air Filter ELPAF62 V13H134AB0

		YCbCr								
Resolution	Refresh Rate (Hz)	4:2:0			4:2:2			4:4:4		
		8	10	12	8	10	12	8	10	12
3840 x 2160	30	Signal does not exist			SDR	HDR*	HDR*	SDR	HDR*	HDR*
3840 x 2160	60	SDR	HDR*	HDR*	SDR	HDR*	HDR*	SDR	HDR*	HDR*
3840 x 2160	120	SDR	SDR	-	SDR	HDR*	HDR*	SDR	-	-

*HDR: Support for HDR10, HDR10+ and HLG.

All images simulated.

1 4K Resolution Enhancement Technology shifts each pixel to produce an image on screen, up to the stated specification. | 2 HDR/HDR10+ performance available with select third-party devices. For more information, see www.epson.com/hdrcompatibility | 3 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 4 Based on TFCinfo: U.S. Projector Brand Customer Perception and Preference Study, Multimedia Projectors 2019. | 5 No required maintenance for the light source for up to 20,000 hours. Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 6 For convenient and reasonable recycling options, visit www.epson.com/recycle | 7 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

&RQWDFWU&KQ&DOXH&HOFWURQLFVFRP



9DO&(OHFWUR&FV)DFWRU&UHFV(SVR&ROG&DOHU

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. PrivateLine and PRO-UHD are registered trademarks, UltraBlack is a trademark and Epson Connection and Extra Care are service marks of Epson America, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks.
 Copyright 2022 Epson America, Inc. Com-SS-Oct-13 CPD-61060 1/22