

# Features and Specifications - Technics - Turntable - SL

Value Electronics, Technics Factory Direct Dealer, Authorized Nationwide USA for Sales

Direct Drive

Brushless DC motor

33-1/3, 45, and 78 rpm The turntable speed will be 78.26 rpm when set to 78 rpm.

0.32 N · m (3.3 kgf · cm), (2.86 lbf-in)

0.7 s. from standstill to 33-1/3 rpm

Electronic brake

0.025% W.R.M.S.

Brass and aluminum die-cast combined Diameter: 332mm (13-5/64") Weight: Approx. 3.6kg (7.9lbs) (Including a

Static Balance

230mm (9-1/16")

15mm (19/32")

Within 2° 32' (at the outer groove 12" record) Within 0° 32' (at the inner groove of 12" record)

Without auxiliary weight: 5.6 - 12.0 g 14.3 - 20.7g (including head shell) With small auxiliary weight: 10.0 - 16.4 g (including head shell) With big auxiliary weight: 14.3 - 19.8 g 23.0 - 28.5g (including head shell)

12.7 mm (1/2") interval

1.2mmφ 4-pin terminal lug

PHONO (Pin Jack) x 1 EARTH TERMINAL x 1

AC120 V, 60 Hz

10 W (Power ON)0.2 W (Power OFF)

453 x 173 x 372 mm17-27/32" x 6-13/16" x 14-21/32" inch

Approx. 13.0 kg28.7lbs

0°C to +40°C (+32°F to +104°F)

35% to 80% RH (no condensation)

Turntable, Turntable sheet, Dust cover, EP record adaptor, Balance weight, Auxiliary weight, Head shell, Overhaul  
Screw set for cartridge, PHONO cable, PHONO earth lead, AC power supply cord, Screw set for turntable, Own



